| ARTICLE CODE | DESCRIPTION |
| --- | --- |
| PPP-5610 | Pallet Solid line - 1140x1140x165mm - open deck - 6 skids - recycled PO |

## BRAND

Cabka

## PRODUCT DESCRIPTION

Reusable pallet suitable for long-term use
Impact-resistant material - without metal reinforcements
Universal, durable and environmentally friendly solution for storage, distribution, closed loops or export, pharmaceuticals & laboratory, healthcare sector, etc.
Suitable for intensive use in high-rotation logistics, semi-hygienic environments
Temperature resistant from -20°C to +40°C, cleaning up to +65°C (max. 10 min.) and short-term surface steaming up to +100°C
Weather and UV resistant
Easy cleaning
Rounded impact zones reduce risk of damage to a minimum
Raised edges ensure optimal transport security and stability
Options: anti-slip structures, customisation, etc.
100% recyclable at end of life
Entry height long side, between runner and deck: 95 mm
Maximum static load: 5000 kg
Maximum dynamic load: 2500 kg
Maximum racking load: 1375 kg
Packaging: 15 pallets/stack







## SPECIFICATIONS

| | |
| --- | --- |
| Length (mm) | 1140 |
| Width (mm) | 1140 |
| Height (mm) | 165 |
| Net weight (kg) | 28.5 |
| Matter | Polyolefins |
| Color | Anthracite |

## TECHNICAL DETAILS

| | |
| --- | --- |
| ETIM | EC004004 |
| MOQ sales (Pc.) | 15 |

## ATTRIBUTES

| | |
|---|---|
| Model | Solid line |
| Gs Certificate | false |
| Quantity Par Stack | 15 |
| Load Capacity Static (kg) | 5000 |
| Load Capacity Dynamic (kg) | 2500 |
| Type Of Surface | Open deck |
| Nestable | false |
| Load Capacity In Rack (kg) | 1375 |
| Entry Height | Entry height between the runner and the deck: 95 mm // |
| Quantity Skids | 6 |