ARTICLE CODE	DESCRIPTION
MKG-4901	Isothermal container Koala Green 495 - 855x1285x1360mm - static cooling - 0°C +10°C - 4 wheels

BRAND

Melform

PRODUCT DESCRIPTION

Static refrigerated container with front door opening and integrated 120 Ah battery on wheels
One-piece moulded inner and outer walls in impact-resistant polyethylene
Suitable for intensive and professional daily use
Insulation core: injected high-density polyurethane, free of CFC- and HCFC
Operating temperature as isothermal container, without active cooling: -20° to +60°C
Temperature control static cooling: 0°C to +10°C
Also available in the following temperature ranges: 0°C to +40°C / -25°C to +10°C / -25°C to +40°C
Static cooling is integrated at the back of the container
3 fixed runners present at 290, 480 and 660 mm from the bottom of the container
Optional grid MKG-9002 available
Forks produced from galvanized steel
Wheel type: rubber tread on PA core, Ø 125 mm
Standard 2 fixed wheels and 2 swivel castors, of which 1 swivel castor with brake
Perfect hygiene thanks to the smooth finish
Internal groove structures for improved air circulation
No weld seams, no sharp edges due to rotomoulded monostructure
Quick and easy to clean
Fully recyclable
Programmable digital thermostat with monitoring function during transport
Durable stainless steel locking handle with practical release button
Hinges in galvanized steel
With integrated stainless steel handles for safe and smooth movement
Overall heat transfer coefficient: K = 0,35 W/m²K
Int. dim.: L850 x W625 x H950 mm
Internal volume: 500 l









SPECIFICATIONS

Length (mm)	855
Width (mm)	1285
Height (mm)	1360
Net weight (kg)	138
Matter	• Insulated polyethylene • Polyurethane
Color	Blue Grey

TECHNICAL DETAILS

Warranty period (M)	12
MOQ sales (Pc.)	1

ATTRIBUTES

Type	Refrigerated container on wheels
Power Source	Replaceable LiFePO4 battery
Model	Koala Green 495
Type Of Handles	Integrated handles
Quantity Handles	2
Temperature Range	-20° to +60°C
Food safe certified	true
Material handle	Stainless steel
Internal height (mm)	950
Internal length (mm)	850
Internal width (mm)	625
Opening side/top	Front door opening
Type of temperature regulation	Programmable digital thermostat
Nominal absorption	0,62A
Fuses	230 Vac 50-60Hz
Place cooling unit	Integrated in the back of the container
Type of cooling unit	Static cooling
Charging time battery life	8/10 hours
Refrigerent gas	R134a
Heat transfer coefficient (W/m^2K)	0.35
Cooling unit included?	true
Amperage battery (Ah)	120
Battery life (h)	14
Included seat for grids?	true
Operating temperature controlled cooling	0°C - +10°C